HDPE FITTINGS · CATALOGUE SIZES

HDPE Socket Fusion Reducing Tee



PRODUCT CONFIGURATION

Material
HDPE

Connection
Socket fusion

Catalogue designation
PN16

Listed configurations
27

Original photograph from the supplied product library. Illustration only; the photo does not identify a specific size or pressure rating.

> Only the size combinations and designations listed in this sheet are covered. Do not assume that every size is available in every pressure class. Complete listed configurations follow on the next page.

BEFORE ORDERING

Send the catalogue code or exact size combination, required rating, quantity and project conditions with your enquiry. Availability is subject to confirmation.

DOCUMENT SCOPE

Technical selection reference prepared from supplied product data. Not a certificate, test report, engineering design or installation instruction.

HDPE FITTINGS · CATALOGUE SIZES

HDPE Socket Fusion Reducing Tee

Listed configurations 1–14 / 27

LISTED CONFIGURATIONS

Catalogue code	Size (mm)	Catalogue rating
T25-20	25 × 20	PN16
T32-20	32 × 20	PN16
T32-25	32 × 25	PN16
T40-20	40 × 20	PN16
T40-25	40 × 25	PN16
T40-32	40 × 32	PN16
T50-20	50 × 20	PN16
T50-25	50 × 25	PN16
T50-32	50 × 32	PN16
T50-40	50 × 40	PN16
T63-20	63 × 20	PN16
T63-25	63 × 25	PN16
T63-32	63 × 32	PN16
T63-40	63 × 40	PN16

Values reproduce the supplied catalogue. Confirm the exact size, material grade, pressure designation, operating conditions and connection compatibility before ordering.

HDPE FITTINGS · CATALOGUE SIZES

HDPE Socket Fusion Reducing Tee

Listed configurations 15–27 / 27

LISTED CONFIGURATIONS

Catalogue code	Size (mm)	Catalogue rating
T63-50	63 × 50	PN16
T75-32	75 × 32	PN16
T75-40	75 × 40	PN16
T75-50	75 × 50	PN16
T75-63	75 × 63	PN16
T90-50	90 × 50	PN16
T90-63	90 × 63	PN16
T90-75	90 × 75	PN16
T110-40	110 × 40	PN16
T110-50	110 × 50	PN16
T110-63	110 × 63	PN16
T110-75	110 × 75	PN16
T110-90	110 × 90	PN16

Values reproduce the supplied catalogue. Confirm the exact size, material grade, pressure designation, operating conditions and connection compatibility before ordering.