PP FITTINGS · DIMENSIONAL REFERENCE

Polypropylene (PP) Clamp Saddle



Original photo from the supplied product library. Illustration of the fitting family only; it does not identify a size, series or pressure rating.

SELECTION SUMMARY

Fitting family
Clamp saddle / outlet

Listed combinations
36

Pressure rating
Confirm for the selected series

This document lists selected size combinations only. It does not establish a pressure class, thread standard, service temperature, drinking-water approval or installation procedure. The complete selected size table follows.

BEFORE ORDERING

Confirm the exact fitting series, pipe size and grade, required pressure, service conditions, quantity and mating connection. Availability is subject to confirmation.

DOCUMENT SCOPE

Selection reference prepared from supplied product data. Not a certificate, test report or engineering design. Sizes not listed must be checked separately.

PP FITTINGS · DIMENSIONAL REFERENCE

Polypropylene (PP) Clamp Saddle

Listed combinations 1–18 / 36

LISTED SIZE COMBINATIONS

Main pipe outside diameter (mm)	Nominal outlet size (in)
20	1/2
25	1/2
25	3/4
32	1/2
32	3/4
32	1
40	1/2
40	3/4
40	1
50	1/2
50	3/4
50	1
50	1 1/4
63	1/2
63	3/4
63	1
63	1 1/4
63	1 1/2

These 36 size combinations are repeated in both supplied saddle schedules, with and without a reinforcing ring. They do not define the actual construction supplied. Confirm the ring, outlet thread, seal and pipe compatibility.

Inch values are nominal catalogue thread sizes. BSP/BSPT/NPT, parallel/tapered form and sealing method are not established by this source and must be confirmed.

PP FITTINGS · DIMENSIONAL REFERENCE

Polypropylene (PP) Clamp Saddle

Listed combinations 19–36 / 36

LISTED SIZE COMBINATIONS

Main pipe outside diameter (mm)	Nominal outlet size (in)
75	1/2
75	3/4
75	1
75	1 1/4
75	1 1/2
75	2
90	1/2
90	3/4
90	1
90	1 1/4
90	1 1/2
90	2
110	1/2
110	3/4
110	1
110	1 1/4
110	1 1/2
110	2

These 36 size combinations are repeated in both supplied saddle schedules, with and without a reinforcing ring. They do not define the actual construction supplied. Confirm the ring, outlet thread, seal and pipe compatibility.

Inch values are nominal catalogue thread sizes. BSP/BSPT/NPT, parallel/tapered form and sealing method are not established by this source and must be confirmed.