PVC SYSTEMS · SELECTED CATALOGUE DATA

PVC-U fittings · selected PN10 / PN16 sizes



DOCUMENT SUMMARY

Selected material
PVC-U

Selection tables
2

Listed fitting combinations
173

Original photograph from the supplied product library. Family illustration only; it does not identify a specific size, material grade, pressure class or certified batch.

Five fitting families from two separate catalogue series. Φ and DN labels are kept separate. This sheet does not cover every fitting or confirm stock. Reviewed tables follow on the next pages.

BEFORE ORDERING

Provide the exact material, size designation, outside diameter, wall series, quantity and service conditions. Confirm current drawings, connection compatibility and availability before ordering.

DOCUMENT LIMITS

Prepared from supplied catalogue data. Not a certificate, test report, installation guide or approval of current standards compliance. Pressure and service suitability require separate confirmation.

PVC SYSTEMS · SELECTED CATALOGUE DATA

PVC-U fittings · water catalogue PN10

REVIEWED CATALOGUE ENTRIES

Fitting family	Listed Φ sizes (mm)
90° elbow	20, 25, 32, 40, 50, 63, 75, 90, 110, 125, 140, 160, 200, 225, 250, 280, 315, 355, 400
45° elbow	20, 25, 32, 40, 50, 63, 75, 90, 110, 125, 140, 160, 200, 225, 250, 280, 315, 355, 400
Equal tee	20, 25, 32, 40, 50, 63, 75, 90, 110, 125, 140, 160, 200, 225, 250, 280, 315, 355, 400
Straight coupler	20, 25, 32, 40, 50, 63, 75, 90, 110, 125, 140, 160, 200, 225, 250, 280, 315, 355, 400
End cap	20, 25, 32, 40, 50, 63, 75, 90, 110, 125, 140, 160, 200, 225, 250, 280, 315, 355, 400

Φ sizes reproduce the water catalogue. PN10 is the source-series label, not an all-temperature working-pressure guarantee. Confirm sockets, cement and pipe compatibility.

Prepared from supplied catalogue data. Not a certificate, test report, installation guide or approval of current standards compliance. Pressure and service suitability require separate confirmation.

PVC SYSTEMS · SELECTED CATALOGUE DATA

PVC-U fittings · industrial catalogue PN16

REVIEWED CATALOGUE ENTRIES

Fitting family	Listed catalogue DN designations
90° elbow	DN15, DN20, DN25, DN32, DN40, DN50, DN65, DN80, DN100, DN125, DN150, DN200, DN250, DN300, DN350, DN400
45° elbow	DN15, DN20, DN25, DN32, DN40, DN50, DN65, DN80, DN100, DN125, DN150, DN200, DN250, DN300, DN350, DN400
Equal tee	DN15, DN20, DN25, DN32, DN40, DN50, DN65, DN80, DN100, DN125, DN150, DN200, DN250, DN300, DN350, DN400
Straight coupler	DN15, DN20, DN25, DN32, DN40, DN50, DN65, DN80, DN100, DN125, DN150, DN200, DN250, DN300, DN350, DN400
End cap	DN15, DN20, DN25, DN32, DN40, DN50, DN65, DN80, DN100, DN125, DN150, DN200, DN250, DN300

DN designations are copied exactly and are not outside diameters in mm. Do not equate them with the Φ sizes on the preceding page. PN16 is the source-series label; verify the actual assembly and service conditions.

Prepared from supplied catalogue data. Not a certificate, test report, installation guide or approval of current standards compliance. Pressure and service suitability require separate confirmation.